

KINGSLEY

GARAGE DOORS SPARES

t. 0800 376 7573 e. sales@kgds.co.uk w. www.kgds.co.uk

INSTRUCTIONS FOR FITTING A CANOPY DOOR WITH REPLACEMENT CD45 CONES AND CABLES & SPRING TENSION ADJUSTMENT DETAILS

CONTENTS LIST		
Part Code	Part Description	QTY
CCTA 0000 L	L/H* Cone Pulley Assembly (White)	1
CCTA 0000 R	R/H* Cone Pulley Assembly (Black)	1
DPIN 0273	4 x 50mm Split Pin	1
DPIN 0280	5/32" x 1" Roll Pin	2
DPINW 5517	Contents List & Fitting Instructions	1
	4mm (5/32") Allen Key	1
	1/4" Toggle Bar	2

* Viewed from Inside

Tools Required

2 off - 22mm Open Ended Spanners (Gedore No7)
Hammer & Spade Ended Screwdriver
Pliers
1/8" Diameter Flat nosed Pin Punch
Small Step Ladder

- * ! WARNING ! * -

The spring is under extreme tension.

Follow the instructions carefully to avoid personnel injury

**IN THE EVENT OF ANY DIFFICULTY PLEASE CONSULT YOUR
LOCAL WESSEX GARAGE DOOR SUPPLIER OR CALL OUR**

HELPLINE ON 01202 825 451

Date: - Jan 2001

DPINW 5517

Issue "B"